LAN · WiFi · WEB · NETIO Cloud · Mobile Application · 19" Rack · DI · Sensor T1 · Sensor TH1 · Power Metering · ZCS Zero Current · ZVS Zero Voltage · PowerUp State · Condition & Rules · Ping WatchDog · Power WatchDog · Scheduler · HTTPs · JSON HTTP(s) · Modbus/TCP · SNMP v1/v2 · SNMP v3 · MQTT-flex · nBus · Telnet · XML HTTP(s) · Push JSON · URL API HTTP(s)

PowerBOX 4Kx

NETIO PowerBOX 4Kx is a LAN-enabled smart power strip with 4 outputs. Each output socket can be switched on or off individually over the web interface. Integration with 3rd party systems using various protocols (JSON over HTTP(s), Modbus/TCP, SNMP, MQTT-flex, Telnet, …) is possible. With the secure NETIO Cloud service, the outputs can be controlled from anywhere. Drivers for AV systems are available (Crestron, Extron, Savant, RTI, Utelogy, ELAN and more).

Power Metering & Switching

SPECIFICATIONS

- Switching & metering each power output independently
- 4x power metering (A, W, kWh, TPF, V, Hz)
- Power input:
  - Fixed cable 1.6m
  - Plug: Type F/E (16A) / Type G (13A)
- Power output: 4x max 16A per output (13A for 4PG)
- 1x RJ45 Ethernet
- ZCS (Zero Current Switching)

FEATURES

- PowerUp Sequence
- PowerUp State / Delay
- Week Scheduler function
- Ping + Power WatchDog
- Condition & Rules
- AV Drivers ready

CONTROL OPTIONS

- Web Interface (HTTPs)
- Open API
- NETIO Cloud
- NETIO Mobile 2

OPEN API

- Telnet
- SNMP v1/v3
- Modbus/TCP
- MQTT-flex
- URL API - HTTP(s) get
- JSON over HTTP(s)

  & more

PowerBOX 4Kx with WiFi

PowerBOX 4Kx **with WiFi** is available. It comes in all three Types of sockets (G, F, E).